

TECHNISCH LEAFLET

ILLBRUCK AFDICHTINGSCOATINGS



	LD925 WATERBASED i-SEAL COATING	OS925 BARRIER SEAL COATING	SP925 FLEXIBLE SEAL COATING
Verkwastbaar	Beperkt	Ja	Ja
Verspuitbaar	Airless spuitapparatuur	Airless spuitapparatuur	Compressor
Type machine*	TSN 11 / 65 Dolphin 15000	TSN 11 / 65 Dolphin 15000	Opbrengst: ≥150l / min Tank: ≥100 l
Tip/ pistool	TIP**: 317/321	TIP**: 441	Pistool: illbruck AA925 Jetflow 600 Combi
Werkdruk	80-100 Bar	100-120 Bar	7-10 Bar

*Onderhoud/schoonmaken i.o.m. leverancier machine

**Indicatief, meerdere mogelijkheden

Verbruik	35-40 m' / 10 kg	70-80 m' / 20 kg	6-10 m' / worst
Laagdikte (nat)	2 mm***	1,5-3 mm***	2 mm
Type Rugvulling	FM330 PERFECT ELASTIC FOAM PRO PR101 PU Rugvulling	FM330 PERFECT ELASTIC FOAM PRO	FM330 PERFECT ELASTIC FOAM PRO PR101 PU Rugvulling
UV- bestendig	Nee	Nee	Nee
Overstucbaar	Ja, zie TDS	Ja, zie TDS	Ja, zie TDS
Kleur(en)	Wit	Zwart	Wit/antraciet

***Minimale laagdikte, afhankelijk van toepassing