

CI/SfB	(31)	Lt3
CAW P10		
Uniclass L681		

Description

ME901 Butyl & Bitumen Primer is a brush applied polymer solution for use with illbruck butyl and bitumen tapes and membranes.

Colour

Transparent

Packaging

1 litre (12 per carton) and 5 litre tins.

Technical Information

Property	Result
Material	Solvent based synthetic rubber
Open Time at +20°C	Approximately 10 minutes
Open Time at +5°C	Approximately 20 minutes
Open Time at 0°C	Approximately 30 minutes
Open Time at -5°C	Approximately 40 minutes
Drying Time	8 hours
Storage	Store in shaded dry conditions between +5°C and 25°C
Shelf Life	6 months when stored as recommended in original unopened containers

* The primer retains a high level of surface tack after drying. Exposed areas (not covered by tape / membrane) may be subject to dirt pick-up.

Preparation

- No special preparation is required, however, surfaces should be sound.
- Best results will be achieved on dry, dust and grease free surfaces.
- Paint residues and impregnating agents must be removed from the adhesion surface.

Application

- Must be used above -5°C.
- Apply evenly and carefully. If necessary mask adjoining surfaces not to be primed.
- After priming the surfaces must be protected against dust, moisture, etc.
- Always store with packaging properly closed.
- The tape or membrane may be applied after approximately 10 minutes at 20°C and after approximately 40 minutes at -5°C.

Coverage

Coverage will depend on the porosity of the substrate. Coverage on rough, porous materials will be reduced. Based on 40 mm wide application strip, 1 litre will yield approximately 100 to 200 linear metres.

Cleaning

Splashes or spills must be removed immediately. Mask and protect adjacent surfaces.



ME901

Butyl & Bitumen Primer

Usage / Purpose

ME901 Butyl & Bitumen Primer is used as a pre-treatment bonding agent and primer when working with illbruck butyl and bitumen tapes and membranes.

Key Benefits

- Improves tape / membrane adhesion on cold or damp surfaces
- Stabilises unsound surfaces
- Improves weathersealing on porous substrates
- Quick drying
- Can be used down to -5°C

Please Note

ME901 Butyl & Bitumen Primer cannot be over-painted as it may dissolve paints, varnishes and some plastics. Testing is recommended prior to application to check compatibility. The information in this datasheet can only provide general indications of performance in use. Because of conditions of use and application, outside of our control and the large number of different materials, the user is advised to test and establish the suitability of the product for his particular application.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer service on 01942 251400.

Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but

which is proved to be defective, will be replaced free of charge.

No liability can be accepted for information provided in this leaflet although it is published in good faith and believed to be concerned. tremco illbruck Limited reserves the right to alter product specification without prior notice, in line with Company policy of continuous development and improvement.



tremco illbruck LLC
W2 B4 • DIRC • DIP 2
PO Box 450539
Dubai • UAE
T: +971 4 8852403
F: +971 4 8854872

mecsu@tremco-illbruck.com
www.tremco-illbruck.com