

CI/SfB	(31)	Lt3
CAW P10		
Uniclass L681		

Description

ME902 is a spray applied polymer solution for use with illbruck butyl and bitumen tapes and membranes.

Colour

Transparent

Packaging

500 ml aerosol can (12 per carton)

Technical Information

Property	Result
Material	Solvent based synthetic rubber
Open Time at +20°C	Approximately 10 minutes
Open Time at +5°C	Approximately 20 minutes
Open Time at 0°C	Approximately 30 minutes
Open Time at -5°C	Approximately 40 minutes
Storage	Store in shaded dry conditions between +5°C and 25°C
Shelf Life	12 months when stored as recommended in original unopened containers

Preparation

- No special preparation is required, however, surfaces should be sound.
- Best results will be achieved on dry, dust and grease free surfaces.
- Paint residues and impregnating agents must be removed from the adhesion surface.

Application

- Minimum application temperature -5°C.
- Spray evenly and thoroughly onto the substrate.
- If the wetting of the surface is insufficient, repeat the process.
- Highly absorbent, dusty substrates or very rough surfaces should be primed using a brush with ME901 Butyl & Bitumen Primer brush grade.
- Cover adjacent surfaces, illbruck PU foam and floor coverings or decorative surfaces before spraying.
- Protect the sprayed surface from dust, moisture, etc.
- If the spray nozzle clogs, clean with a cloth and illbruck PU foam gun cleaner AA290.

Coverage

Coverage will depend on the porosity of the substrate. Based on 40 mm wide application strip, 1 aerosol can will yield approximately 50 linear metres.

Cleaning

Overspray should be removed immediately using illbruck PU foam gun cleaner AA290.



ME902

Butyl & Bitumen Spray Primer

Usage / Purpose

ME902 Butyl & Bitumen Spray Primer serves as a bonding agent and primer for the application of illbruck membranes incorporating butyl and bitumen adhesives.

Key Benefits

- Easy spray application
- Increases final bond strength
- Improves adhesion of illbruck membranes
- Short drying time

ME902

Butyl & Bitumen Spray Primer



Please Note

Protect adjacent areas (and polyurethane foams) with masking tape or otherwise protect them from spray mist. Paints, varnishes and plastics can be dissolved. Compatibility with adjacent materials must be tested.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer service on 01942 251400.

Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but

which is proved to be defective, will be replaced free of charge.

No liability can be accepted for information provided in this leaflet although it is published in good faith and believed to be concerned. tremco illbruck Limited reserves the right to alter product specification without prior notice, in line with Company policy of continuous development and improvement.



tremco illbruck LLC
W2 B4 • DIRC • DIP 2
PO Box 450539
Dubai • UAE
T: +971 4 8852403
F: +971 4 8854872

mecsu@tremco-illbruck.com
www.tremco-illbruck.com