

### Description

OT301 is a dispersion based on acrylic copolymers and ethanol.

### Colour

Green

### Packaging

Item No.	Content
340604	310 ml cartridge (20 per carton)

### Coverage

Content	Bead	Coverage
310 ml	5 mm	Approx. 15 m
310 ml	8 mm	Approx. 6 m
310 ml	10 mm	Approx. 4 m

### Technical Information

Property	Result
Material	Dispersion based on acrylic copolymers and ethanol - free from plasticisers, halogens
Characteristics	Durable, elastic
System	Physically drying
Curing Time	2 – 3 days depending on substrate, humidity and membrane
Density	Approx. 1.2 g/cm <sup>3</sup>
Application Temperature	-10°C to + 50°C
Temperature Resistance	permanent -20°C to +80°C
Storage	Store in shaded dry conditions between -20°C and +25°C During the storage period the viscosity will increase
Shelf Life	1 year when stored as recommended in original unopened packaging

### Application

- Surfaces must be dry and free of oil, grease, dust and other anti-adhesive components. Mineral substrates (such as plaster or concrete), may be slightly damp.
- Bonding to frozen surfaces is not possible.
- Substrates must offer sufficient load-bearing capacity. It may be necessary to use a mechanical support (pressure lath) for example on crumbling substrates.
- Joints are possible on mineral substrates, on planed and painted wood, high density plastic and non-rusting metal (e.g. pipes, windows etc.), and hardboard (chipboard, OSB, veneer plywood and MDF board).
- The user is responsible for checking the suitability of the substrate. Adhesion tests are recommended. Some surfaces may require priming with ME904 primer. If in doubt, please contact tremco illbruck Technical Services.


### Health & Safety Precautions

Safety data sheet must be read and understood before use.



**OT301**

## Endurance Adhesive



### Usage / Purpose

Use OT301 for creating airtight joints between illbruck vapour barrier and structural elements, airtightness membranes, wall lining membranes of all kinds and for bonding wind-tight joints between sub-roof and roof-lining membranes. A permanent bond is achieved on all illbruck membranes, PE, PA, PP and aluminium foil used to create an airtight seal.

### Key Benefits

- Very high, permanent adhesion
- Quick drying
- No pressure lath is required on loadbearing substrates
- Very elastic, permanently flexible
- Can be applied in low temperatures and suitable for permanent use in very wide temperature range
- Can be stored in very low temperatures

OT301

## Endurance Adhesive



---

### Technical Service

tremco illbruck has a team of experienced Technical Service Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Service on 01942 251400.

### Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has

been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. tremco illbruck Ltd. reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



### tremco illbruck Limited

Coupland Road, Hindley Green  
WN2 4HT Wigan  
United Kingdom  
T: +44 1942 251400  
F: +44 1942 251410

info.uk@tremco-illbruck.com  
www.tremco-illbruck.co.uk