

Description

AA291 produces a corrosion resistant, non-stick coating, suitable for lubrication, unblocking, sliding and protecting materials such as metal and plastics. The spray is extremely versatile and can be used for many applications around the house, in the garage and garden, on windows and doors in cars, vans, trucks and boats, garden machinery etc. to lubricate moving parts such as screws, nuts, hinges, stays, locks, chains, sliders, tools, taps and valves. It can be used as a high temperature anti-seize coating between dissimilar metals such as steel, brass, copper, aluminium, zinc etc. It will protect against the effects of salt water spray and immersion. Ideal for maintenance of PU Foam guns, avoiding blockages.

Packaging

200 ml aerosol cans with spray nozzle (12 per carton)

Protective Equipment

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Technical Information

Characteristic	Results (Typical Values)
Composition	Base mixture of mineral and gasoline oil
Density	0.695 kg/m ³
Flash Point	Below 0°C
Fire Classification DIN 4102-1	B (Flammable)
Temperature Resistance (after drying)	-50°C to +250°C
Application Temperature	+5°C to +35°C
Storage	Store in shaded, dry conditions between +5°C and +25°C
Shelf Life	12 months when stored as recommended in original, unopened containers

Preparation

Before use, shake the canister well and repeat during use.

Application

- For maintenance of PU Foam guns, unscrew the empty foam canister from the gun.
- Clean the gun nozzle and screw adaptor thoroughly with AA290 PU Solvent Cleaner.
- Spray the AA291 on the cleaned screw adapter and nozzle prior to fitting a new PU Foam canister.
- For general applications, spray the AA291 sparingly onto the surface to be treated, maintaining the canister 300 mm from the surface.
- Allow 5 minutes for the coating to dry completely. If convenient, components can be coated and stored under clean and dry conditions and assembled later.



AA291

Lubricant Spray

Usage / Purpose

AA291 Lubricant Spray is an aerosol applied Teflon based CFC, HFC and HCFC free non-staining lubricant for use on metal and plastic moving parts. It produces a dry, low friction, non-stick protective coating that is hard wearing and long lasting. AA291 is ideal for the maintenance of PU Foam guns.

Key Benefits

- Universal use
- Ideal for maintenance of PU Foam guns
- High adhesion
- Salt water resistant
- Neutral pH

AA291

Lubricant Spray



Health & Safety Precautions

Safety data sheet must be read and understood before use.
Extremely flammable - keep away from open flames and other ignition sources.

Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco

illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



tremco illbruck Limited
Coupland Road, Hindley Green
WN2 4HT Wigan
United Kingdom
T: +44 1942 251400
F: +44 1942 251410

info.uk@tremco-illbruck.com
www.tremco-illbruck.co.uk