

Description

AW444 is an 80 micron protection tape manufactured to an FR standard and embossed to give anti-slip properties.

Colour

Milky

Packaging

Item No.	Roll Width	Roll Length
347821	600 mm	100 m

Technical Information

Property	Result
Fire Behaviour (EN 13501-1:2018)	B _{fl}
Smoke Production (EN 13501-1:2018)	s1
Relative Humidity	~ 80% ±10%
Backing Material	LDPE (with special edition)
Type of Adhesive	Water based acrylic
Backing Tensile Strength (MD)	>18 N/25 mm
Backing Tensile Strength (TD)	>12 N/25 mm
Adhesion	~ 650 g/25 mm ±10%
Elongation at Break (MD)	>280%
Elongation at Break (TD)	>330%
Application Temperature	+10°C to +40°C
Storage	Store rolls indoors in shaded dry conditions between +10°C & +25°C
Shelf Life	12 months from date of production when stored as recommended in original unopened packaging

Application Conditions

- Ensure carpet is dry.
- Apply in temperatures between +10°C and +40°C.
- The tape should be removed (and if necessary replaced) 3 months maximum after application as UV exposure is likely to make subsequent removal difficult.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Please Note

The above data and recommendations are given in good faith, on the basis of practical experience, but without warranty. The customer should carry out their own tests to confirm the suitability of the product for the application under consideration.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



AW444

FR Embossed Carpet Tape

Usage / Purpose

AW444 Embossed Carpet Protection Film is a self-adhesive film suitable for application to carpet and other surfaces requiring temporary protection against damage during processing and storage or resulting from other trades activity once installed.

The film must be removed and potentially replaced at a maximum 3 months following application due to potential UV degradation causing difficult removal.

Key Benefits

- Manufactured to meet the standard B1 EN 13501-1:2018
- Protects carpets from mortar, render or paint splatter
- Easy application
- Easy removal



Tremco CPG UK Limited
Coupland Road
Hindley Green, Wigan WN2 4HT
United Kingdom
T: +44 1942 251400
F: +44 1942 251410

info.uk@cpg-europe.com
www.cpg-europe.com